

## 4262 Exhaust Gas Analyzer Tubing



### Features

- Temperature Range: -40°F to 200°F (-40°C to 93°C)
- Smooth Core Tube Resists Hydrocarbon Deposit Buildup
- Special Polymer Cover Provides Excellent Temperature Resistance
- Very Flexible, Flame Retardant
- Bonded Co-Extruded Construction for Kink Resistance; Resistant to Vacuum Collapse

### Construction

- Special Black Polymer Exterior
- Nylon Lined

### Applications

- Emissions Analysis
- Low Pressure Pneumatics

Part Number	Nominal I.D.		Nominal O.D.				Wall		Minimum Bend Radius		Maximum Working Pressure		Weight	
			Maximum		Minimum								lbs/100 ft	kg/100 m
	in	mm	in	mm	in	mm	in	mm	psi	bar				
4262-4010	.260	6.6	.445	11.3	.415	10.5	.090	2.2	3/4	19	50	3	4.6	6.8
4262-4020	.250	6.4	.460	11.7	.430	10.9	.098	2.4	3/4	19	50	3	5.0	7.4
4262-5030	.312	7.9	.527	13.4	.497	12.6	.100	2.5	7/8	22	50	3	6.1	9.0

## 4207/4233 Weed Spray Tubing



### Features

- Core Tube Resists Hydrocarbon Deposit Buildup
- Offers Excellent Kink Resistance, Good Resistance to Vacuum Collapse
- Lightweight for Easier Handling
- Provides Higher Temperature Resistance and Excellent Flexibility
- 4207 Is a Single Layer Wall Design for Maximum Strength
- 4233 Contains Three Flexible Layers for Maximum Flexibility

### Construction

- Bonded Co-Extruded Nylon Construction (4233)
- Natural Nylon Tube (4207)

### Applications

- Weed Spray Control
- Horticultural Spray

Part Number	Nominal I.D.		Nominal O.D.		Wall Thickness		Minimum Burst Pressure @ 75°F		Weight	
	in	mm	in	mm	in	mm	psi	bar	lbs/100 ft	kg/100 m
	4207-12754	.375	9.5	.525	13.3	.075	1.9	1,300	90	3.3
4207-16754	.500	12.7	.650	16.5	.075	1.9	700	48	6.5	9.6
4233-0875	.510	13.0	.650	16.5	.075	1.9	250	17	6.5	9.6